



## ibml ImageTrac 6300

The ImageTrac 6300 class scanners provide an efficient document scanning solution that helps organizations improve the productivity of their prep, scan and downstream processes by maximizing efficiencies and reducing exceptions – all while delivering superior reliability.

The ImageTrac 6300 class scanners are designed for applications with moderate amounts of in-line processing and are available with either one or two out-sort pockets.

**The ImageTrac 6300 class scanners are ideal for a range of applications, including:**

- Medical records scanning
- Mortgage processing
- Tax processing
- Claims processing
- Application processing
- Lockbox processing
- Back-file conversion
- Service bureau/shared services processing
- Digital mailroom

The ImageTrac 6300 class is available in two speed options, 286 pages per minute and 429 pages per minute (based on 8.5" x 11" documents with a 2" gap at 200 DPI).

In addition to providing high-quality, efficient processing at exceptional speeds, the ImageTrac 6300 class scanners also reduce document preparation cost by allowing for the scanning of documents of multiple sizes and thicknesses in a single pass. This means that document prep workers have fewer prep exceptions and steps to contend with in getting batches prepared for scanning.

The ImageTrac 6300 class scanners also provide dual multi-feed detection to help eliminate downstream errors. When a double-feed is detected, the ImageTrac scanning track automatically stops to allow for recovery. Our doubles detection technology ensures that all pages are scanned and eliminates the need for operators to do a post-scan review to account for all images.

**The ImageTrac 6300 has the ability to expand and be upgraded to the 6400 class scanner. This assures that if your needs change or operation grows so can your ImageTrac.**

The ImageTrac 6300 class scanners are powered by ibml's proven SoftTrac capture software for improved operational control, scanning accuracy and document processing. Built for the shared services approach, SoftTrac allows operators to manage scanning activities from an easy-to-use touch screen. It also provides the ability to manage scanning activities from a single console.

## BENEFITS

- Reduced document preparation
- Fewer jams/fast jam recovery
- Increased operator productivity
- Reduced operations expense
- Less downtime/easy maintenance
- Fewer downstream exceptions
- Potential to finish scan work earlier in the day
- Ergonomically enhanced

## FEATURES

- Throughput speeds of 286 pages per minute and 429 ppm with the high speed option
- Duplex camera imaging
- Mixed document scanning
- Bitonal, grayscale and color scanning
- DynamicTIFF
- Ultrasonic doubles detection
- Multi-feed detection
- Mechanical document detection and de-skew
- Single High Capacity Full Page Pocket
- User-friendly color touch screen

## OPTIONS

- Single pocket with run-out tray
- Additional sort pocket
- Thick document
- Envelope detection
- Hardware barcode reader
- Pre- and post-image ink jet printer
- Hardware MICR reader
- Up to 21 pockets
- JPEG 2000
- DocNetics® Suite

# ibml ImageTrac 6300

## High Volume and sorter document scanner

### RATED THROUGHPUT SPEEDS IN LANDSCAPE ORIENTATION

Camera Resolution DPI	Letter (ppm)	A4 (ppm)	Checks (ppm)	A6 (ppm)
300	286	292	632	489
200 with High Speed Option	429	438	947	733

Maximum document size	297 mm x 432 mm (11,7 inches x 17 inches)
Minimum document size	64 mm x 85 mm (2,5 inches x 3,25 inches)
Paper thickness and weight	Standard feeder 45 g/m <sup>2</sup> to 200 g/m <sup>2</sup> ; Asian paper (rice paper) to card stock
Multi-Feed detection	Ultrasonic sensor and friction technology
Feeder capacity	1.500 sheets (20# bond paper)

OPTIONS		ibml ImageTrac 6300
Hardware	Barcode reader	Yes
	Patch code reader	Yes
	Single-Head ink jet printer	Pre and/or Post-Image
	Multi-Head ink jet printer	Pre-Image
	MICR-E13B	Yes
	MIR-CMC7	Yes
	Sort pockets	Single pocket with run-out tray; Standard High Capacity Full Page Pockets, can hold up to 1.200 documents.
Software	SoftracScan	Yes
	Docnetics Suite	Yes

SCANNER FEATURES		ibml ImageTrac 6300
Multi-Feed detection		Single or multiple ultrasonic sensor technology and/or friction multi-feed detection
Color touch screen control		Operator control via 23" wide screen color LCD panel touch screen
Illumination		Dual LED illumination patented technology
Image output types		JPEG (color/gray scale images); TIFF (black and white images); JPEG 2000
Resolution	Optical	300 dpi
	Output	Black and White/Color/Gray scale: 150 to 600 dpi; Scaling range limited to 1/2x to 2x from optical camera dpi.
Image processing		Dynamic TIFF Thresholding; Speckle Removal; Auto crop; Auto-Deskew; Image Rotation; Multi-image Output; Color Dropout, sRGB Color Space Support, etc.
Environmental factors		RoHS compliant
Acoustical noise		Operating mode 77.4db(A)
Heat dissipation		6.000 to 15.000 BTUs/hour
Operating humidity		20% to 80% non-condensing (percent relative humidity)
Operating temperature		50 to 90 degrees (F), 10 to 32 degrees (C)
Shipping/Storage temperature		22 to 140 degrees (F), -30 to 60 degrees (C)
Altitude		Sea level to 10.000 ft (3.048 M)
Power options		110 VAC North America or 220 VAC International
Electrical requirements		United States: 208V~, 2 Wire + GND25A 50/60 Hz; European Union: 230V~, 1 Wire + PE (single phase) 25A 50/60 Hz; Japan: 200V~, 2 Wire + GND25A 50/60 Hz; US Sites - Units shipped with power cord and 208-240V, NEMA #L6-30 connector; Non US sites - Power cable supplied by customer to meet local electrical code
Machine dimensions (Width/Length/Height)		822,45 mm x 2.488,69 mm x 1.227,58 mm ( 32,38 inches x 97,98 inches x 48,33 inches)
Weight		Feeder frame: 102,51 kg (226 lbs); Front camera frame: 128,82 kg (284 lbs); Pocket frame: 106,59 kg (235 lbs)
Host		Embedded Application Controller

Minimum gap and throughput will vary based on the specific application processing requirements.

Spigraph: 31, Boucle de la Ramée – BP 749 - 38 297 Saint-Quentin-Fallavier Cedex – France | [www.spigraph.com](http://www.spigraph.com) | Tel.: +33 (0)4 74 94 62 60 | All the brands and logotypes, registered or not, are the property of their respective owners. ©2015 Spigraph and Imaging Business Machine. All rights reserved. Datasheet No. NETW-1040-EN

